

DWG. No.: 1000302352

Date Prepared: 2022/11/01

Date Revised: 2024/01/30

Product Name: "EX" for initial filling oil

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: "EX" for initial filling oil

1.2 Relevant identified uses of substance or mixture and uses advised against

Recommended use: General industrial application

1.3 Details of the supplier of the safety data sheet

Identification of the

supplier: KOBELCO COMPRESSORS CORPORATION

Address: ON Building, 9-12, Kita-Shinagawa 5-chome, Shinagawa-ku, Tokyo,

141-8688, Japan

1.4 Emergency telephone number

Emergency telephone

number: +81-3-5739-5341

2. Hazards identification

2.1 Classification of the substance or mixture

Hazard category Category

No Classification Flammable liquids Acute toxicity (oral) No Classification Acute toxicity (dermal) No Classification Acute toxicity(dust, mist) No Classification Skin corrosion/irritation No Classification Serious eye damage/eye irritation No Classification Aspiration hazard No Classification Acute hazards to the aquatic environment No Classification

2.2 Label elements

Hazard pictograms: Not applicable
Signal word: Not applicable
Hazard statement: Not applicable

Precautionary statements:

Prevention Do not handle until all safety precautions have been read and

understood.

Wear protective gloves/protective clothing/eye protection/face

protection.

Do not allow the eyes to become exposed to the product. Do not

swallow the product.

Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product.



DWG. No.: 1000302352 Date Prepared: 2022/11/01 Date Revised: 2024/01/30

Product Name: "EX" for initial filling oil

Response IF SWALLOWED: Immediately call a POISON CENTER/doctor.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

If the eyes are exposed to the product: Rinse the eyes with plenty

of running water and immediately contact a physician.

IF ON SKIN: Wash with plenty of soap and water.

Storage The product must be stored in a cool, well-ventilated location

where it will not be exposed to direct sunlight.

Containers that have been opened must be tightly sealed.

Disposal Dispose of contents/container in accordance with

local/regional/national/international regulations.

If there are any doubts about proper methods of handling the product, contact the point of purchase before proceeding with

usage.

2.3 Other hazards

PBT or vPvB : Not applicable

3. Composition/information on ingredients

3.1 Substances Not Applicable

3.2 Mixtures

Ingredients and Concentration

Ingredient Name	Concentrationwt.%
Base 0il(s)	90-99
Additives	<10

4. First aid measures

4.1 Description of first aid measures

Inhalation: IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

Cover the body with blankets to keep warm and quiet. If you feel

unwell, seek medical advice.

Skin contact: Immediately flush skin with large amounts of water.

Wash contaminated clothing before reuse.

If skin irritation occurs: Get medical advice/attention.

Eye contact: Rinse with clean water carefully for several minutes. Remove

contact lenses if present and if removal is easy, then continue rinsing. Rinse for 15 minutes at a minimum and seek medical

attention.



DWG. No.: 1000302352 Date Prepared: 2022/11/01 Date Revised: 2024/01/30

Product Name: "EX" for initial filling oil

Ingestion: Do not induce vomiting. Drink [one glass] [two glasses] of water.

Call a physician [or poison control

center] immediately.

4.2 Most important symptoms and effects, both acute and delayed

No information for mixtures.

No information.

4.3 Indication of any immediate medical attention and special treatment needed.

No information for mixtures.

5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: Mist of loaded liquid, dry chemicals, carbon dioxide, fire foam,

and dry sand are effective.

Extinguishing media to avoid: Use of straight stream of water can cause a risk of spreading

fire.

5.2 Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical:

In some cases of fire, may release irritant gases.

When burnt, may generate carbon monoxide and other toxic gases.

Fire fighting: Spray water to the surrounding facilities for cooling.

Keep unauthorized persons off the site of occurrence of fire and

the surroundings.

Even after extinction, cool containers thoroughly with plenty of

water.

5.3 Advice for fire-fighters

Special protective equipment and precautions for fire fighters:

Wear fire resistant or flame retardant clothing.

Fight fire from windward direction while wearing protective equipment. If contact with skin is expected, wear impervious

protective equipment and gloves.

Use air-breathing apparatus and protective clothing whenever

necessary.

6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency measures

Wear protective equipment when working.

Remove nearby potential ignition sources immediately.

When mist is generated, use respiratory equipment to prevent

inhalation of mist.

Do not touch or walk through spillage.



DWG. No.: 1000302352 Date Prepared: 2022/11/01 Date Revised: 2024/01/30

Product Name: "EX" for initial filling oil

Pay attention to the site of spillage, which is slippery.

6.2 Environmental precautions

Prevent spreading of oil spill with earth and sand, sandbags, or other proper materials and use care not to allow the oil spill to flow to street drains, sewer systems, and rivers.

At sea, install oil spill containment booms to prevent spreading of spills and absorb with absorption mat or other proper materials.

6.3 Methods and material for containment and cleaning up

In case of spillage in small quantity, collect spillage by absorbing with earth, sand, sawdust, waste, or other proper materials.

In case of spillage in large quantity, enclose with embankment to prevent spreading of spillage and collect spillage in empty containers to the extent possible.

6.4 Reference to other sections

In case of spillage, immediately inform the organizations concerned of the spillage to prevent possible accidents and spreading of spillage.

Remove nearby potential ignition sources immediately and make fire-extinguishing agents available. Remove spillage completely, and ventilate and clean the site and the surroundings.

7. Handling and storage

7.1 Precautions for safe handling

Technical measures:

Keep away from any possible contact with sparks, open flames, and high-temperature materials, and do not allow release of vapor without justification.

Use pumps or other proper equipment for taking out from containers. Do not siphon with your mouth using a tube. Do not drink.

When mist is generated, use respiratory equipment to prevent inhalation of mist.

In case of vapor/mist dispersion, install a closed system, local ventilation system, and/or other proper equipment for the sources of vapor/mist generation.

Avoid rough handling of containers such as falling, dropping, exposing to shock, and dragging.

Ventilation requirements:

Maintain adequate ventilation when handling indoors.

Precautions for safe handling:

Avoid falling, dropping, exposing to shock, or dragging of containers.

Wash hands and face thoroughly after handling.



DWG. No.: 1000302352

Date Prepared: 2022/11/01

Date Revised: 2024/01/30

Product Name: "EX" for initial filling oil

Be careful with fire.

Wear protective gloves when opening containers to eliminate a risk

of hand injury.

Contact avoidance: Use care to keep away from any possible contact with halogens,

strong acids, alkalis, and acidifying substances.

Contact with and storage in the same location of halogens, strong

acids, alkali and oxidized substances must be avoided.

Hygiene measures: After handling Wash hands thoroughly.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a well ventilated, cool, dry, dark place, protecting from

direct sunlight and keeping away from any potential ignition

sources and high-temperature materials.

Store tightly stopped after use to prevent possible contamination

with dust and moisture.

Preferably store locked up in a proper storage area.

Safety Use spill-proof containers that are free of damage/corrosion. adequate container materials:

7.3 Specific end use(s)

General industrial application

8. Exposure controls/personal protection

8.1 Control parameters

Ingredient Name	Japan Society for Occupational Health	ACGIH	
	Occupational Exposure Limits	TLV-STEL	TLV-TWA
Base 0i1(s)	-ppm 3mg/m3(Mineral Oil Mist)	-ppm -mg/m3	-ppm 5mg/m3(Mineral Oil Mist)

8.2 Exposure controls

Appropriate In case of mist generation, enclose the source of mist generation,

engineering controls: or install a ventilation system.

Install eye cleaning and body cleaning equipment near the handling

site.

Respiratory Not needed under normal conditions, but wear a gas mask (against

protection: organic gases) whenever required.

Hand protection: In case of prolonged or repeated exposure, wear oil-resistant hand

protection.



DWG. No.: 1000302352 Date Prepared: 2022/11/01 Date Revised: 2024/01/30

Product Name: "EX" for initial filling oil

Eye/face protection: In case of exposure to splashes, wear ordinary type goggles.

Skin protection: In case of handling over a prolonged period of time or in case of

exposure to oil, wear oil-resistant, long-sleeved work clothing.

Hygiene measures: Take off contaminated clothing and wash thoroughly before reuse.

Wash hands thoroughly after handling.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Liquid Form: Liquid

Color: Light yellow Odor: Slight odor

Melting point/freezing Pour Point-37.5(℃)

point:

Initial boiling point

and boiling range:

Initial boiling point - End point No data

Flammability (solid,

gas):

Upper/lower ExplosionLimit(1-7vol%)

flammability or explosive limits:

Flash point: ≥200(°C)Cleveland Open Cup

No data

Auto-ignition Estimate $200-410\,(^{\circ}\text{C})$

temperature:

Decomposition No data.

temperature:

pH: No data

Kinematic viscosity: $>20.5 \text{(mm2/sec)} (40^{\circ}\text{C})$ Solubility: water: Insoluble.

Partition coefficient: No data.

n-octanol/water:

Vapour pressure: No data
Density(g/cm3): 0.8459(15℃)
Vapour density: No data.
Particle No data

characteristics:

.



DWG. No.: 1000302352

Date Prepared: 2022/11/01

Date Revised: 2024/01/30

Product Name: "EX" for initial filling oil

10. Stability and reactivity

10.1 Reactivity

Not Reactive

Stable when stored or preserved in a dark place at room temperature.

10.2 Chemical stability

Stable when stored or preserved in a dark place at room temperature.

10.3 Possibility of hazardous reactions

Keep away from any possible contact with strong oxidizing agents.

10.4 Conditions to avoid

Contact with incompatible hazard substances

Prolonged heating, open flames, and ignition sources

10.5 Incompatible materials

Use care to keep away from any possible contact with halogens, strong acids, alkalis, and acidifying substances.

10.6 Hazardous decomposition products

When burnt, may release carbon monoxide and other gases.

11. Toxicological information

11.1 Information on toxicological effects

Product

Acute toxicity (oral): No Classification

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Acute toxicity (dermal): No Classification

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Acute toxicity (inhalation): Classification not possible (Gas)

Classification not possible (Vapour)

No Classification (Dust/Mist)

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Skin corrosion/irritation: No Classification

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Serious eye damage/irritation: No Classification

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Respiratory sensitization: Classification not possible

For mixtures, hazard category was identified based on the

classification criteria for mixtures.



DWG. No.: 1000302352 Date Prepared: 2022/11/01 Date Revised: 2024/01/30

Product Name: "EX" for initial filling oil

> Skin sensitization: Classification not possible

> > For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Mutagenicity: Classification not possible

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Carcinogenicity: Classification not possible

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Classification not possible Reproductive toxicity:

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Target organ effect/Single

exposure:

Classification not possible

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Target organ effect/Multi

exposure:

Classification not possible

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Respiratory toxic: No Classification

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Ingredient Base 0il(s)

> Classification not possible Acute toxicity (oral):

LC50: > 5000 mg/kg[rat]

Classification not possible Acute toxicity (dermal):

LC50:> 5000 mg/kg[rat]

Acute toxicity (inhalation): Classification not possible (Gas)

> Classification not possible (Vapour) Classification not possible (Dust/Mist)

LC50: > 5 mg/L[rat]

Skin corrosion/irritation: Classification not possible Serious eye damage/irritation: Classification not possible

Practically None

Respiratory sensitization:

Classification not possible Classification not possible Skin sensitization:

None Buehler method [guinea pig]

Mutagenicity: Classification not possible

Ames Test: Negative



DWG. No.: 1000302352 Date Prepared: 2022/11/01 Date Revised: 2024/01/30

Product Name: "EX" for initial filling oil

Carcinogenicity: No Classification

EU: Category 2: R45 need not apply. (NOTE L is Applicable),

IARC:3

Reproductive toxicity: Classification not possible
Target organ effect/Single Classification not possible

ranget organ erreet/t

exposure:

Target organ effect/Multi

exposure:

Respiratory toxic: Classification not possible

12. Ecological information

Product

12.1 Toxicity

Ecotoxicity

Acute toxicity: No Classification

Fish: For mixtures, hazard category was identified based on the

Classification not possible

classification criteria for mixtures.

Daphnia: No information.

Algae: For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Chronic toxicity:

Fish: For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Daphnia: No information.

Algae: For mixtures, hazard category was identified based on the

classification criteria for mixtures.

 $12.\,2\ \mathsf{Persistence}\ \mathsf{and}\ \mathsf{degradability}$

Persistence and degradability: No information available on mixtures

12.3 Bioaccumulative potential

Bioaccumulative potential: No information for mixtures.

12.4 Mobility in soil

Mobility in soil: No information for mixtures. Hazardous to the ozone layer: Classification not possible

12.5 Results of PBT and vPvB assessment

Not applicable

12.6 Other adverse effects Other impact:

No information for mixtures.



DWG. No.: 1000302352 Date Prepared: 2022/11/01 Date Revised: 2024/01/30

Product Name: "EX" for initial filling oil

Ingredient

Base Oil(s)

Ecotoxicity

Acute toxicity: Classification not possible

Fish: 96hLC50:> 5000 mg/L[Oncorhynchus mykiss]
Daphnia: 48hEC50:> 1000 mg/L[Daphnia magna]

Chronic toxicity: Classification not possible Hazardous to the ozone layer: Classification not possible

13. Disposal considerations

13.1 Waste treatment methods

Dispose of contents/container in accordance with local/regional/national/international regulations.

Every customer/user of the product should dispose of industrial waste on its own responsibility, otherwise it must rely on a company authorized by prefectural governor for treating industrial waste or a local public body involved in the disposal of industrial waste for proper disposal.

Before disposal of used container, remove contents completely.

13.2 Other information

No additional information

14. Transport information

14.1 UN Number:

IATA UN number: Not regulated IMDG UN number: Not regulated

14.2 UN proper shipping name:

IATA Proper shipping name: Not regulated

IMDG Proper shipping name: Not regulated

14.3 Transport hazard class(es):

IATA UN classification: Not regulated IMDG UN classification: Not regulated

14.4 Packing group:

IATA Packing group: Not regulated IMDG Packing group: Not regulated Domestic restriction: No information.

14.5 Special precautions for user:

Transport containers without causing any significant friction or

shaking.



DWG. No.: 1000302352 Date Prepared: 2022/11/01 Date Revised: 2024/01/30

Product Name: "EX" for initial filling oil

15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance

Australia(AICS):

Canada(DSL):

All components are listed or exempted.

China(IECSC):

All components are listed or exempted.

EU(REACH): In the case where one or more components are not listed or, even if listed,

in the case of importing to the country or area concerned, an application or

notification is required.

Korea(K-REACH): In the case where one or more components are not listed or, even if listed,

in the case of importing to the country or area concerned, an application or

notification is required.

New Zealand(NZIoC):

All components are listed or exempted.

Philippines(PICCS):

All components are listed or exempted.

All components are listed or exempted.

USA(TSCA):

All components are listed or exempted.

15.2 Chemical safety assessment

Not conducted

16. Other information

Reference No information.

Disclaimer: We at HOKUETSU INDUSTRIES CO., LTD have prepared the copyrighted Safety Data

Sheet to provide reference information on the hazardous chemical product of

interest for our customers/users to ensure secure and safe handling.

We would like every customer/user of the product to refer to the information and understand the necessity of taking appropriate measures for the actual handling conditions on their own responsibilities for optimum practical

application of the product of interest.

Consequently, the Safety Data Sheet is not intended to guarantee the safety

of the product referenced to herein.